



TECHNICAL DATA SHEET

RAM Petrolatum Mastic M

DESCRIPTION

The **RAM Petrolatum Mastic M** consists of a compound being made of microcrystalline waxes, oils and inert fillers.

Being 100% manufactured from mulched up petrolatum tape and utilising the advantages of microcrystalline waxes over paraffin waxes AIWC can deliver a product that can be used successfully in the any season of the year.

USES

The **RAM Petrolatum Mastic M** was specifically designed for easy moulding / filling for profiling around flanges, fittings, nuts, bolts and other irregular shapes to achieve a streamline contours for subsequent tape wrapping.

CHARACTERISTICS

Self supporting compound that does not harden. Chemically inert and resistant to moisture.

Specific Gravity: 1.1 Approximately

Weight: 3KG Block (min)

Colour: Brown

VOC Content: None

APPLICATION

Temperature Range: Application -5°C to 45°C. Service Maximum 65°C.

PRODUCTION

RAM Petrolatum Mastic M is produced in one of the newest and most modern plants in the world. The quality control department constantly and continuously monitors the raw materials, the production and packaging in order to ensure a high quality product.



AUSTRALASIAN INDUSTRIAL WRAPPINGS AND COATINGS PTY LTD
49 JEDDA ROAD PRESTONS 2171 NSW AUSTRALIA

TEL : +61 2 9608 8111

FAX : +61 2 8783 7055

EMAIL: enquiries@aiwc.com.au

