



MATERIAL SAFETY DATA SHEET

FLEXI CLAD 40

PRODUCT IDENTIFICATION

- MANUFACTURER'S NAME: Australasian Industrial Wrappings & Coatings P/L
- REGULAR TELEPHONE NUMBER: 02 9608 8111
- EMERGENCY TELEPHONE NUMBER: 0419 242 638
- FACSIMILE NUMBER: 02 8783 7055
- ADDRESS: PO BOX 40, MILLER NSW 2168
- PRODUCT NAME: **FLEXICLAD 40.**
- SYNONYMS: Flexi Clad Tape.
- MANUFACTURER'S CODE: 705 - - -

INGREDIENTS.

- MATERIAL OR COMPONENT NIL
- PERCENTAGE: NIL
- HAZARD DATA: n/a

PHYSICAL DATA

- CHEMICAL ENTITY: Butyl Rubber with Bitumen, PVC backing.
- BOILING POINT: n/a
- SPECIFIC GRAVITY [H2 0.1] 1.1
- VAPOUR DENSITY [AIR.1] n/a
- % VOLATILES BY VOLUME: <1
- APPEARANCE AND ODOUR: Black adhesive tape with slight rubber odour.
- MELTING POINT: n/a
- VAPOUR PRESSURE: None
- SOLUBILITY IN H2O[% BY WT]: n/a
- EVAPORATION RATE [BUTYL ACETATE.1]: Not Volatile
- FLAMM. LIMIT LEL: n/a

FIRE AND EXPLOSION DATA.

- FLAMMABLE LIMITS IN AIR % BY VOLUME: Greater than 250°C
- EXTINGUISHING MEDIA: Foam, Water or CO2.
- SPECIAL FIRE FIGHTING PROCEDURES: Class B procedures.
- UNUSUAL FIRE AND EXPLOSION HAZARD: None known.

HEALTH AND HAZARD DATA

- HEALTH HAZARD DATA:
- ROUTES OF EXPOSURE:- No data supplied.
- INHALATION: n/a
- SKIN CONTACT: Non irritant.



MATERIAL SAFETY DATA SHEET

FLEXI CLAD 40

- SKIN ABSORPTION: n/a
- EYE CONTACT: Treat as foreign object.
- INGESTION: Non toxic
- EFFECTS OF OVER-EXPOSURE: n/a
- ACUTE OVEREXPOSURE: n/a
- CHRONIC OVER-EXPOSURE: n/a
- EMERGENCY AND FIRST AID PROCEDURES:-
- EYES: Irrigate thoroughly with water
- SKIN: Wash thoroughly with soap and water
- INHALATION: n/a
- INGESTION: Do not induce vomiting
- NOTES TO PHYSICIAN: Treat with sympathy.

SPILL OR LEAK DATA

- STEPS TO BE TAKEN IF MATERIAL IS RELEASED n/a
- OR SPILLED:
- NEUTRALIZING CHEMICALS: n/a
- WASTE DISPOSAL METHOD: Non hazardous waste.

SPECIAL PROTECTION INFORMATION

- VENTILATION REQUIREMENTS: No special requirements
- SPECIFIC PERSONAL PROTECTIVE EQUIPMENT: None
- RESPIRATORY [SPECIFY IN DETAIL]: n/a
- EYE: n/a
- GLOVES: Recommended for prolonged or repeated handling.
Grease resistant.
- OTHER CLOTHING AND EQUIPMENT:

REACTIVITY DATA:

- CONDITIONS CONTRIBUTING TO INSTABILITY: None known.
- INCOMPATIBILITY: n/a
- HAZARDOUS DECOMPOSITION PRODUCTS: Smoke, Fumes, Carbon compounds and other decomposition products



MATERIAL SAFETY DATA SHEET

FLEXI CLAD 40

SPECIAL PRECAUTIONS

PRECAUTIONARY STATEMENTS:

FLEXICLAD 40 is a butyl based product which may affect the skin.

USERS ARE RECOMMENDED TO:

Wash thoroughly after use and before work breaks to remove compound from the skin.

Do not use paraffin or other solvents to clean the skin.

Change clothing when soiled.

OTHER HANDLING AND STORAGE

REQUIREMENTS:

Store in original packaging in a cool place away from boilers or heaters

PREPARED BY:

Roger McElhone

ADDRESS:

PO BOX 40, MILLER NSW 2168

DATE:

1st DECEMBER 2019

AUSTRALASIAN INDUSTRIAL WRAPPINGS AND COATINGS PTY LTD
PO BOX 40, MILLER 2168 NSW AUSTRALIA

TEL : 02 9608 8111
FAX : 02 8783 7055
EMAIL: enquiries@aiwc.com.au
WEB: www.aiwc.com.au

