



## MATERIAL SAFETY DATA SHEET

### **FLEXI SEAL 1000**

#### PRODUCT IDENTIFICATION

- MANUFACTURER'S NAME: Australasian Industrial Wrappings & Coatings P/L
- REGULAR TELEPHONE NUMBER: 02 9608 8111
- EMERGENCY TELEPHONE NUMBER: 0419 242 638
- FACSIMILE NUMBER: 02 8783 7055
- ADDRESS: 49 JEDDA ROAD, PRESTONS NSW 2170
- PRODUCT NAME: **FLEXI SEAL 1000.**
- SYNONYMS: Flexi Seal Tape.
- MANUFACTURER'S CODE: 701 - - -

#### INGREDIENTS

- MATERIAL OR COMPONENT: NIL
- PERCENTAGE: NIL
- HAZARD DATA: n/a

#### PHYSICAL DATA

- CHEMICAL ENTITY: Polythene Sheet with SBS/ Bitumen/ Polyisobutylene compound adhesive.
- BOILING POINT: n/a
- SPECIFIC GRAVITY [H2 0.1]: n/a
- VAPOUR DENSITY [AIR.1]: n/a
- % VOLATILES BY VOLUME: <1
- APPEARANCE AND ODOUR: Black solid tape with no odour.
- MELTING POINT: n/a
- VAPOUR PRESSURE: 98°C
- SOLUBILITY IN H2O[% BY WT]: n/a
- EVAPORATION RATE [BUTYL ACETATE.1]: n/a
- FLAMM. LIMIT LEL: n/a

#### FIRE AND EXPLOSION DATA

- FLAMMABLE LIMITS IN AIR % BY VOLUME: Greater than 250°C
- EXTINGUISHING MEDIA: Carbon Dioxide, dry powder, chemical foam.
- SPECIAL FIRE FIGHTING PROCEDURES: None known.
- UNUSUAL FIRE AND EXPLOSION HAZARD: None known.

## HEALTH & HAZARD INFORMATION

- HEALTH HAZARD DATA:
- ROUTES OF EXPOSURE:- No data supplied.
- INHALATION: No adverse effects expected.
- SKIN CONTACT: Contact with skin may result in irritation.
- SKIN ABSORPTION: n/a
- EYE CONTACT: May cause irritation.
- INGESTION: Not acutely toxic
- EFFECTS OF OVER-EXPOSURE: n/a
- ACUTE OVEREXPOSURE: n/a
- CHRONIC OVER-EXPOSURE: n/a
- EMERGENCY AND FIRST AID PROCEDURES:-
- EYES: Irrigate thoroughly with water
- SKIN: Wash thoroughly with soap and water
- INHALATION: n/a
- INGESTION: Do not induce vomiting
- NOTES TO PHYSICIAN: Treat with sympathy.

## SPILL OR LEAK DATA

- STEPS TO BE TAKEN IF MATERIAL IS RELEASED n/a
- OR SPILLED:
- NEUTRALIZING CHEMICALS: n/a
- WASTE DISPOSAL METHOD: No data supplied.

## SPECIAL PROTECTION INFORMATION

- VENTILATION REQUIREMENTS: No special requirements
- SPECIFIC PERSONAL PROTECTIVE EQUIPMENT: None
- RESPIRATORY [SPECIFY IN DETAIL]: n/a
- EYE: n/a
- GLOVES: Recommended for prolonged or repeated handling.  
Grease resistant.
- OTHER CLOTHING AND EQUIPMENT:

## REACTIVITY DATA:

CONDITIONS CONTRIBUTING TO INSTABILITY:	None known.
INCOMPATIBILITY:	n/a
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon dioxide, carbon monoxide, oil fume.

## SPECIAL PRECAUTIONS

PRECAUTIONARY STATEMENTS:	FLEXI SEAL 1000 contains petroleum based products which may affect the skin.
USERS ARE RECOMMENDED TO:	Wash thoroughly after use and before work breaks to remove compound from the skin.  Do not use paraffin or other solvents to clean the skin.  Change clothing when soiled.

## OTHER HANDLING AND STORAGE

REQUIREMENTS:	Store in original packaging in a cool place away from boilers or heaters
PREPARED BY:	Roger McElhone
ADDRESS:	10 / 7 LYN PDE, PRESTONS NSW 2170
DATE:	1 AUGUST 2016



AUSTRALASIAN INDUSTRIAL WRAPPINGS AND COATINGS PTY LTD  
49 JEDDA ROAD PRESTONS 2171 NSW AUSTRALIA  
TEL : 02 9608 8111  
FAX : 02 8783 7055  
EMAIL: [enquiries@aiwc.com.au](mailto:enquiries@aiwc.com.au)  
WEB: [www.aiwc.com.au](http://www.aiwc.com.au)

