

MATERIAL SAFETY DATA SHEET

RAM PETROLATUM PRIMER

PRODUCT IDENTIFICATION

- MANUFACTURER'S NAME:
- REGULAR TELEPHONE NUMBER:
- EMERGENCY TELEPHONE NUMBER:
- FACSIMILE NUMBER:
- ADDRESS:
- PRODUCT NAME:
- SYNONYMS:
- MANUFACTURER'S CODE:

100 - - -

02 9608 8111

0419 242 638

02 8783 7055

• USES:

Corrosion Inhibitor. Primer.

RAM PETROLATUM PRIMER

49 JEDDA ROAD, PRESTONS NSW 2170

Australasian Industrial Wrappings & Coatings P/L

HAZARD IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDINGING TO SAFE WORK AUSTRALIA CRITERIA.

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE.

UN.No: None allocated. DG Class: None allocated Subsidiary Risk: None allocated.

Packing Group: None allocated Hazchem Code: None allocated.

COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT	FORMULA	CAS No.	CONTENT
PETROLATUM WAX	NOT AVAILABLE	NOT AVAILABLE	>60%
FILLER	NOT AVAILABLE	NOT AVAILABLE	NOT AVAILABLE
INHIBITORS	NOT AVAILABLE	NOT AVAILABLE	NOT AVAILABLE

FIRST AID MEASURES

Eye If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poison Information Centre, a doctor, or for at least 15 minutes.
 Inhalation If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.
 Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a poison Information Centre or a doctor.
 Ingestion For advice contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed do not induce vomiting.

Advice to Doctor Treat Symptomatically.

AUSTRALASIAN INDUSTRIAL WRAPPINGS & COATINGS PTY LTD

ADDRESS: 49 Jedda Road, Prestons 2170 NSW Australia TELEPHONE: 02 9608 8111 FAX: 02 8783 7055 EMAIL: enquiries@aiwc.com.au WEB: www.aiwc.com.au





MATERIAL SAFETY DATA SHEET

RAM PETROLATUM PRIMER

FIRE FIGHTING MEASURES

Flammability Combustible. May evolve toxic gases (Carbon oxides, hydrocarbons) when heated to decomposition.

- Fire and Explosion Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use water fog to cool intact containers and nearby storage areas.
- **Extinguishing** Dry agent, carbon dioxide or foam. Prevent contamination of drains or waterways.

Hazchem Code None allocated.

ACCIDENTAL RELEASE MEASURES

SpillageContact emergency services where appropriate. Use personal protective equipment. Clear
area of all unprotected personnel. Ventilate area where possible. Contain spillage, then
cover/ absorb spill with non – combustible absorbent material (vermiculite, sand or similar),
collect and place in suitable containers for disposal. CAUTION: Spill site may be slippery.

STORAGE AND HANDLING

- StorageStore in cool, dry well ventilated area, removed from oxidising agents, acids, heat or ignition
sources and food stuffs. Ensure containers are adequately labelled, protected from physical
damage and sealed when not in use. Large storage areas should have appropriate ventilation
system. Store as a Class C1 Combustible Liquid (AS1940). Also store removed from aromic
solvents.
- HandlingBefore use carefully read the product label. Use of safe work practices are recommended to
avoid eye or skin contact and inhalation. Observe good personnel hygiene. Including washing
hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Stds

Ingredient	Reference	TWA	STEL
Paraffin wax (fume)	ASCC (AUS)	- 2mg/m3	

Biological Limits No biological limit allocated.

Engineering Controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exits, mechanical extraction ventilation is recommended. Maintain vapour levels below the recommended exposure standard.

AUSTRALASIAN INDUSTRIAL WRAPPINGS & COATINGS PTY LTD ADDRESS: 49 Jedda Road, Prestons 2170 NSW Australia TELEPHONE: 02 9608 8111 FAX: 02 8783 7055 EMAIL: enquiries@aiwc.com.au WEB: www.aiwc.com.au



MATERIAL SAFETY DATA SHEET



RAM PETROLATUM PRIMER

PPE Wear splash-proof goggles and nitrile or neoprene gloves. When using large quantities or where heavy contamination is likely, wear: coneralla. Where an inhalation risk exists, wear: a Type A (Organic vapour) respiration.

PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Green or brown grease	Solubility (water)	Insoluble
Odour	Slight odour	Specific Gravity	1.1 (Approx)
Ph	Not available	% Volatiles	0%
Vapour Pressure	e Not available	Flammability	Class C2 Combustible
Vapour Density	Not available	Flash Point	>180 °C
Boiling Point	Not available	Upper Explosion Limit	Not available

Evaporation RateNot available

STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended conditions of storage.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources.
Material to avoid	Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), heat and ignition sources. Also incompatible with aromatic solvents.

Hazardous Decomposition May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

Hazardous Reactions Polymerization is not expected to occur.

TOXICOLOGY INFORMATION

 Health Hazard Summary
 Low toxicity. This product has the potential to cause adverse health effects with direct eye contact, prolonged skin contact or vapour inhalation in poorly ventilated areas. Use safe work practices to avoid eye contact and vapour generation – inhalation.

EyeLow to moderate irritant. Contact may result in irritation, lacrimation, pain and
redness.


InhalationLow to moderate irritant. Over exposure may result in irritation of the nose and
throat, coughing, dizziness and headache.

Skin Irritant. Contact may result in drying and defatting of the skin, rash and dermatitis.

AUSTRALASIAN INDUSTRIAL WRAPPINGS & COATINGS PTY LTD

ADDRESS: 49 Jedda Road, Prestons 2170 NSW Australia TELEPHONE: 02 9608 8111 FAX: 02 8783 7055 EMAIL: enquiries@aiwc.com.au WEB: www.aiwc.com.au





AUSTRALASIAN INDUSTRIAL WRAPPINGS & COATINGS PTY LTD ADDRESS: 49 Jedda Road, Prestons 2170 NSW Australia TELEPHONE: 02 9608 8111 FAX: 02 8783 7055 EMAIL: enquiries@aiwc.com.au WEB: www.aiwc.com.au

