



TECHNICAL DATA SHEET

FLEXISEAL PAVING TAPE

DESCRIPTION

FlexiSeal Paving Tape is a composite membrane of nonwoven Geotextile and self-adhesive rubberised bitumen with high strength and high elongation properties.

USES

It is designed as a joint sealant and reflective crack inhibitor, providing stress relief and waterproofing in concrete and asphalt pavements. It is also used to seal the joints of concrete culverts and bridge decks.

APPLICATION

Ensure surface is clean and dry. Prime porous surfaces with **Flexi Seal Primer**. Lay the membrane onto the surface and press firmly into place.

CHARACTERISTICS

Physical Properties	Typical Value	Test Method
Thickness @ 2 kPa Pressure	1.8mm	AS 3706.1
Wide Strip Tensile Strength	7.5 KN/m	AS 3706.2
Wide Strip Tensile Elongation	50%	AS 3706.2
Puncture Strength	300 N	ASTM D4833

PRODUCTION

FlexiSeal Paving Tape is produced in one of the newest and most modern plants in the world. The quality control department constantly and continuously monitors the raw materials, the production and packaging in order to ensure a high quality product.

Sizes, article and batch numbers are indicated on each roll.

AUSTRALASIAN INDUSTRIAL WRAPPINGS & COATINGS PTY LTD

ADDRESS: 49 Jedda Road, Prestons 2170 NSW Australia

TELEPHONE: 02 9608 8111

FAX: 02 8783 7055

EMAIL: enquiries@aiwc.com.au

WEB: www.aiwc.com.au

