

RAM MASTIC M

PRODUCT IDENTIFICATION

MANUFACTURER'S NAME: Australasian Industrial Wrappings & Coatings P/L

REGULAR TELEPHONE NUMBER: 02 9608 8111
EMERGENCY TELEPHONE NUMBER: 0419 242 638
FACSIMILE NUMBER: 02 8783 7055

ADDRESS:
49 JEDDA ROAD, PRESTONS NSW 2170

PRODUCT NAME: RAM MASTIC M

SYNONYMS:

MANUFACTURER'S CODE: 201 - - USES: Filler, Mastic.

HAZARDS IDENTIFICATION

Not classified as hazardous according to safe work Australia criteria.

Not classified as a dangerous good by the criteria of the ADG code.

UN No: None allocated.

DG Class: None allocated.

Subsidiary Risks: None allocated.

Packing Group: None allocated.

Hazchem Code: None allocated.

COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredients	Formula	CAS. No	Content.
PETROLATUM	NOT AVAILABLE.	NOT AVAILABLE	≻ 60%

FIRST AID MEASURES

EYE: If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing

until advised to stop by a Poison Information Centre, a doctor, or for at least 15 minutes.

Inhalation: If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

Skin: If contact with hot material occurs, drench area immediately with cold water. DO NOT

attempt to remove material adheres to the skin. Seek immediate medical attention

AUSTRALASIAN INDUSTRIAL WRAPPINGS & COATINGS PTY LTD

ADDRESS: 49 Jedda Road, Prestons 2170 NSW Australia

TELEPHONE: 02 9608 8111

FAX: 02 8783 7055





RAM MASTIC M

Ingestion: For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at

once). If swallowed, do not induce vomiting. Ingestion is considered unlikely due to product

form.

Advice to doctor: Treat symptomatically.

FIRE FIGHTING MEASURES

Flammability: Combustible. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to

decomposition.

Fire and Explosion: Evacuate area and contact emergency services. Toxic gases may be evolved in a fire

situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self contained breathing apparatus (SCBA) when combating fire. Use

water frog to cool intact containers and nearby storage areas.

Extinguishing: Dry agent, carbon dioxide or foam. Prevent contamination of drains and water ways.

Hazchem Code: None allocated.

ACCIDENTAL RELEASE MEASURES.

Spillage: If spilt, collect and reuse where possible. Use personal protective equipment. Contain pillage,

then collect and place in suitable containers for disposal. Prevent spill entering drains or

water ways.

STORAGE AND HANDLING

Storage: Store in a cool, dry, well ventilated area where possible. Use personal protective

equipment. Contain spillage, then collect and place in suitable containers for

disposal. Prevent spill entering drains or waterways.

Handling: Before use carefully read the product label. Use of safe work practices are

recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking, smoking

in contaminated areas.

EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Stds: No exposure standards allocated.

Biological Limits: No biological limit allocated.

Engineering Controls: Avoid inhalation. Use in well ventilated areas.

AUSTRALASIAN INDUSTRIAL WRAPPINGS & COATINGS PTY LTD

ADDRESS: 49 Jedda Road, Prestons 2170 NSW Australia

TELEPHONE: 02 9608 8111

FAX: 02 8783 7055





RAM MASTIC M

PPE: Wear splash – proof goggles. When using large quantities or where heavy

contamination is likely, wear: coveralls. Individuals with sensitive skin should

consider wearing; PVC or rubber gloves.

PHYSICAL AND CHEMICAL PROPERTIES.

Appearance: DARK BROWN PUTTY Solubility (water): INSOLUBLE

Odour: MILD ODOUR Specific Gravity: 1.05

Ph: NEUTRAL % Volatiles: NOT AVAILABLE

Vapour Pressure: NOT AVAILABLE Flammability: COMBUSTIBLE

Vapour Density: NOT AVAILABLE **Flash Point:** 240°C (oc)

Boiling Point: NOT AVAILABLE Upper Explosion Limit: NOT AVAILABLE

Melting Point: NOT AVAILABLE Lower Explosion Limit: NOT AVAILABLE

Evaporation Rate: NOT AVAILABLE Auto-ignition Temperature: NOT AVAILABLE

Partition Coefficient: NOT AVAILABLE Decomposition Temperature: NOT AVAILABLE

Viscosity: NOT AVAILABLE

STABILITY AND REACTIVITY:

Chemical Stability: Stable under recommended conditions of storage.

Conditions to avoid: Avoid shock, friction, heavy impact, heat, sparks, open flames and other ignition

sources.

Material to Avoid Incompatible with oxidising agents and acids. (eg. Nitric acid)

Hazardous Decomposition Products:

May evolve toxic gases (carbon oxides, hydrocarbons) when heated to

decomposition.

Hazardous Reactions: Polymerization is not expected to occur.

TOXICOLOGICAL INFORMATION:

Health Hazard Summary: Non-irritant – low toxicity. When in the solid or semi solid form, no adverse health

effects are anticipated. If heated, direct contact with the molten material may result

in burns. Use safe work practices to avoid eye or skin contact and inhalation.

AUSTRALASIAN INDUSTRIAL WRAPPINGS & COATINGS PTY LTD

ADDRESS: 49 Jedda Road, Prestons 2170 NSW Australia

TELEPHONE: 02 9608 8111

FAX: 02 8783 7055





RAM MASTIC M

Eye: Low to moderate irritant. Contact my result in irritation, lacrimation, pain and

redness.

Inhalation: Not irritant. In solid/ semi solid form, an inhalation hazard is not anticipated. Over

exposure to fumes (if heated) may result in irritation of the nose and throat, with

nausea and headache.

Skin: Low irritant, prolonged or repeated contact may result in mild irritation.

Ingestion: Low toxicity. Ingestion may result in gastrointestinal irritation. However, due to

product form ingestion is considered unlikely. Maintain good personal hygiene

standards.

Toxicity Data: PETROLATUM (Not available) - LD50 (Intraperitoneal): > 50g/kg (mouse)

ECOLOGICAL INFORMATION:

Environment: Limited ecotoxicity data was available for this product at the time this report was

prepared. Ensure appropriate measures are taken to prevent this product from

entering the environment.

DISPOSAL CONSIDERATIONS

Water Disposal: Reuse where possible. Alternatively, absorb with sand or similar and dispose of to

an approved landfill site. Contact the manufacturer for additional information.

Legislation: Dispose of in accordance with relevant local legislation.

TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE.

Shipping Name: None allocated. **UN N.O:** None allocated.

Packing Group: None allocated. DG. Class: None allocated

Hazchem Code: None allocated Subsidiary Risks: None allocated

REGULATORY INFORMATION

Poison Schedule: A poison schedule number has not been allocated to this product using the criteria in the

Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

OTHER HANDLING AND STORAGE

AUSTRALASIAN INDUSTRIAL WRAPPINGS & COATINGS PTY LTD

ADDRESS: 49 Jedda Road, Prestons 2170 NSW Australia

TELEPHONE: 02 9608 8111

FAX: 02 8783 7055





RAM MASTIC M

REQUIREMENTS: Store in original packaging in a cool place away from boilers or

heaters

PREPARED BY: Roger McElhone

ADDRESS: 49 JEDDA RD, PRESTONS NSW 2170

DATE: December 2019

AUSTRALASIAN INDUSTRIAL WRAPPINGS & COATINGS PTY LTD

ADDRESS: 49 Jedda Road, Prestons 2170 NSW Australia

TELEPHONE: 02 9608 8111

FAX: 02 8783 7055

