



MATERIAL SAFETY DATA SHEET

FLEXI SEAL PRIMER

PRODUCT IDENTIFICATION

- MANUFACTURER'S NAME: Australasian Industrial Wrappings & Coatings P/L
- REGULAR TELEPHONE NUMBER: 02 9608 8111
- EMERGENCY TELEPHONE NUMBER: 0419 242 638
- FACSIMILE NUMBER: 02 8783 7055
- ADDRESS: 49 JEDDA ROAD, PRESTONS NSW 2170
- PRODUCT NAME: FLEXI SEAL PRIMER
- SYNONYMS: - Flexi Seal Primer
- MANUFACTURER'S CODE: 700004 & 700020

IDENTIFICATION

UN Number: 1993
Dangerous Goods Class and Subsidiary Risk: 3
Hazchem Code: 2W
Packaging Group: III
Correct shipping name: Tars and liquid
Poison schedule number: 5

Use: Primer for metal surfaces before applying Flexi Seal tapes. Applied using brush, roller or spray.

PHYSICAL DESCRIPTION / PROPERTIES

Appearance: Black liquid
Flash point (OC): 31°C closed cup
Vapour pressure: Not available
Specific Gravity: 0.95
Flammability Limits: 1.0 - 7.5
Solubility in water: Negligible

INGREDIENTS

This product contains no hazardous ingredients

Chemical Name:	CAS Number:	Proportion:
Bitumen (blown)	64742-93-4	30-60%
Mineral turpentine	64742-95-6	30-60%

AUSTRALASIAN INDUSTRIAL WRAPPINGS AND COATINGS PTY LTD

49 JEDDA ROAD PRESTONS, NSW, 2171, AUSTRALIA

TEL: +61 2 9608 8111. FAX: +61 2 87873 7055

EMAIL: enquiries@aiwc.com.au. WEB: www.aiwc.com.au





MATERIAL SAFETY DATA SHEET

FLEXI SEAL PRIMER

HEALTH HAZARD INFORMATION

Swallowed: Toxic. May cause nausea and irritation to the gastrointestinal tract.

Eye: May cause irritation

Skin: May cause skin irritation

Inhaled: High vapour concentrations are irritating to the respiratory tract. Swallowing may cause lung damage. May cause dizziness, headaches and nausea. Can produce central nervous system depression if exposure levels are exceeded resulting in loss of coordination, impaired judgement and loss of consciousness.

Chronic Prolonged or repeated exposure to solvents can result in contact dermatitis. Repeated over exposure to vapours may adversely affect the central nervous system, respiratory system and renal system. Health effects are due to the solvent contained in the product.

FIRST AID

Storage: Store in a cool, dry well ventilated area, removed from oxidising agents, acids and foodstuffs. Ensure containers are adequately labelled.

Handling: Before use carefully read the product label. Use of work safe practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Stds:

Ingredient	Reference	TWA		STEL	
		Ppm	mg/m3	Ppm	mg/m3
Mineral Oil Mist	ASCC (AUS)	-	5.0	-	-
Paraffin Wax (fume)	ASCC (AUS)	-	2.0	-	-
Talc (no asbestos fibres)	ASCC (AUS)	-	2.5	-	-



AUSTRALASIAN INDUSTRIAL WRAPPINGS AND COATINGS PTY LTD

49 JEDDA ROAD PRESTONS, NSW, 2171, AUSTRALIA

TEL: +61 2 9608 8111. FAX: +61 2 87873 7055

EMAIL: enquiries@aiwc.com.au. WEB: www.aiwc.com.au